


定格総荷重表 200t吊クローラークレーン(KH1000)

単位:t

ブーム長さm 作業半径m	33.0m	36.0m	39.0m	42.0m	45.0m	48.0m	51.0m	54.0m	57.0m	60.0m	63.0m
7.6	100.0										
8.0	100.0										
9.0	100.0	100.0	87.3								
10.0	85.8	85.7	84.1	80.1	75.8						
14.0	53.2	53.0	52.7	52.6	52.4	52.4	52.3	50.9	47.5		
18.0	38.0	37.8	37.5	37.3	37.1	37.1	37.1	36.8	36.8	36.7	35.9
20.0	33.1	32.9	32.6	32.4	32.2	32.2	32.1	31.9	31.8	31.8	31.5
22.0	29.2	29.0	28.7	28.5	28.3	28.3	28.3	28.0	27.9	27.9	27.6
24.0	26.1	25.9	25.9	25.4	25.2	25.2	25.1	24.8	24.8	24.7	24.4
26.0	23.5	23.3	23.0	22.8	22.6	22.6	22.5	22.2	22.2	22.1	21.8
28.0	21.4	21.2	20.8	20.6	20.4	20.4	20.3	20.0	20.0	19.9	19.6
30.0	19.6	19.4	19.0	18.8	18.6	18.5	18.4	18.2	18.1	18.0	17.8
32.0		17.8	17.4	17.2	17.0	17.0	16.8	16.6	16.5	16.4	16.2
36.0				14.7	14.4	14.4	14.2	14.0	13.9	13.8	13.6
40.0					12.5	12.4	12.2	12.0	11.9	11.8	11.5
44.0							10.6	10.4	10.2	10.2	9.9
48.0								9.7	9.5	9.5	9.2
52.0								9.1	8.9	8.8	8.6
56.0									8.4	7.8	7.5

フックブロック質量 (ton)

フックの種類	200t用	100t用	60t用	25t用	12.5t用
質量	2.6	1.4	1.2	0.85	0.5



## 第26吉野号

(200tクローラークレーン搭載)

第26吉野号	尺度 1:500
KH1000 定格総荷重表	H24.07.01
吉野建設株式会社	